

Reg. No. :

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

**Question Paper Code : 51620**

B.E./B.Tech. DEGREE EXAMINATION, MAY/JUNE 2014.

Third Semester

Mechanical Engineering

ME 2202/ME 33/ME 1201/080190005/10122 ME 303/AT 2203/AT 36/  
10122 AU 302 — ENGINEERING THERMODYNAMICS

(Common to Automobile Engineering)

(Regulations 2008/2010)

(Common to PTME 2202 Engineering Thermodynamics for B.E. (Part-Time) Third Semester Mechanical Engineering – Regulation 2009)

Time : Three hours

Maximum : 100 marks

(Use of approved thermodynamics tables, Mollier diagram, Psychometric chart and Refrigerant property tables permitted in the Examination)

Answer ALL questions.

PART A — (10 × 2 = 20 marks)

1. Define: Thermodynamic Equilibrium.
2. Differentiate between Point function and Path function.
3. State: Kelvin-Planck statement.
4. Write Carnot theorem and its corollaries.
5. Draw a p-T (pressure-temperature) diagram for a pure substance.
6. Mention the possible ways to increase thermal efficiency of Rankine cycle.
7. What are the assumptions made to derive ideal gas equation analytically using the kinetic theory of gases?

8. Using Clausius-Claperyon's equation, estimate the enthalpy of vaporization at  $200^{\circ}\text{C}$  :  $v_g = 0.1274 \text{ m}^3/\text{kg}$ ;  $v_f = 0.001157 \text{ m}^3/\text{kg}$ ;  $dp/dT = 32 \text{ kPa/K}$ .
9. Define: Adiabatic saturation temperature.
10. What is by-pass factor?

PART B — ( $5 \times 16 = 80$  marks)

11. (a) Determine the heat transfer and its direction for a system in which a perfect gas having molecular weight of 6 is compressed from  $101.3 \text{ kPa}$ ,  $20^{\circ}\text{C}$  to a pressure of  $600 \text{ kPa}$  following the law  $pV^{1.3} = \text{constant}$ . Take specific heat at constant pressure of gas as  $1.7 \text{ kJ/kg.K}$ .

Or

- (b) In a gas turbine installation air is heated inside heat exchanger up to  $750^{\circ}\text{C}$  from ambient temperature of  $27^{\circ}\text{C}$ . Hot air then enters into gas turbine with the velocity of  $50 \text{ m/s}$  and leaves at  $600^{\circ}\text{C}$ . Air leaving turbine enters a nozzle at  $60 \text{ m/s}$  velocity and leaves nozzle at temperature of  $500^{\circ}\text{C}$ . For unit mass flow rate of air, determine the following assuming adiabatic expansion in turbine and nozzle,
- Heat transfer to air in heat exchanger
  - Power output from turbine
  - Velocity at exit of nozzle. Take  $c_p$  for air as  $1.005 \text{ kJ/kg}^{\circ}\text{K}$ .
12. (a) (i) A reversible heat pump is used to maintain a temperature of  $0^{\circ}\text{C}$  in a refrigerator when it rejects the heat to the surroundings at  $25^{\circ}\text{C}$ . If the heat removal rate from the refrigerator is  $1440 \text{ kJ/min}$ , determine the C.O.P. of the machine and work input required.
- (ii) If the required input to run the pump is developed by a reversible engine which receives heat at  $380^{\circ}\text{C}$  and rejects heat to atmosphere, then determine the overall C.O.P. of the system.

Or

- (b)  $5 \text{ m}^3$  of air at  $2 \text{ bar}$ ,  $27^{\circ}\text{C}$  is compressed up to  $6 \text{ bar}$  pressure following  $pv^{1.3} = \text{constant}$ . It is subsequently expanded adiabatically to  $2 \text{ bar}$ . Considering the two processes to be reversible, determine the network, net heat transfer, change in entropy. Also plot the processes on T-S and P-V diagrams.

13. (a) A vessel having a capacity of  $0.05 \text{ m}^3$  contains a mixture of saturated water and saturated steam at a temperature of  $245^\circ\text{C}$ . The mass of the liquid present is  $10 \text{ kg}$ . Find the following
- The pressure,
  - The mass,
  - The specific volume,
  - The specific enthalpy,
  - The specific entropy, and
  - The specific internal energy.

Or

- (b) A steam power plant operates on a theoretical reheat cycle. Steam at boiler at  $150 \text{ bar}$ ,  $550^\circ\text{C}$  expands through the high pressure turbine. It is reheated at a constant pressure of  $40 \text{ bar}$  to  $550^\circ\text{C}$  and expands through the low pressure turbine to a condenser at  $0.1 \text{ bar}$ . Draw T-s and h-s diagrams. Find:
- Quality of steam at turbine exhaust
  - Cycle efficiency
  - Steam rate in  $\text{kg/kWh}$ .

14. (a) Derive the Maxwell relations and explain their importance in thermodynamics.

Or

- (b) The pressure and temperature of mixture of  $4 \text{ kg}$  of  $\text{O}_2$  and  $6 \text{ kg}$  of  $\text{N}_2$  are  $4 \text{ bar}$  and  $27^\circ\text{C}$  respectively. For the mixture determine the following:
- The mole fraction of each component ;
  - The average molecular weight;
  - The specific gas constant;
  - The volume and density:
  - The partial pressures and partial volumes.

15. (a) An air-water vapour mixture enters an air-conditioning unit at a pressure of  $1.0 \text{ bar}$ ,  $38^\circ\text{C}$  DBT, and a relative humidity of  $75\%$ . The mass of dry air entering is  $1 \text{ kg/s}$ . The air-vapour mixture leaves the air-conditioning unit at  $1.0 \text{ bar}$ ,  $18^\circ\text{C}$ ,  $85\%$  relative humidity. The moisture condensed leaves at  $18^\circ\text{C}$ .

Determine the heat transfer rate for the process.

Or

- (b) It is required to design an air-conditioning system for an industrial process for the following hot and wet summer conditions

Outdoor conditions                      32°C DBT and 65% RH.

Required air inlet conditions    25°C DBT and 60% RH.

Amount of free air circulated    250 m<sup>3</sup>/min

Coil dew temperature                13°C.

The required condition is achieved by first cooling and dehumidifying and then by heating. Calculate the following (Solve this problem with the use of psychrometric chart):

- (i) The cooling capacity of the cooling coil and its by-pass factor.
  - (ii) Heating capacity of the heating coil in kW and surface temperature of the heating coil if the by-pass factor is 0.3.
  - (iii) The mass of water vapour removed per hour.
-